US 20170280265A1

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2017/0280265 A1

Po (43) Pub. Date: Sep. 28, 2017

(54) METHOD TO DETERMINE LOUDSPEAKER CHANGE OF PLACEMENT

(71) Applicant: **APPLE INC.**, Cupertino, CA (US)

(72) Inventor: **Bruce C. Po**, (US)

(21) Appl. No.: **15/514,455**

(22) PCT Filed: **Sep. 29, 2015**

(86) PCT No.: **PCT/US2015/053014**

§ 371 (c)(1),
(2) Date: **Mar. 24, 2017**

Related U.S. Application Data

(60) Provisional application No. 62/057,999, filed on Sep. 30, 2014.

Publication Classification

(51) **Int. Cl.**

H04S 7/00	(2006.01)
H04R 3/12	(2006.01)
G06F 3/16	(2006.01)
H04R 3/04	(2006.01)
H04R 1/40	(2006.01)

(52) **U.S. Cl.**

CPC ***H04S 7/302*** (2013.01); ***H04R 3/04*** (2013.01); ***H04R 1/403*** (2013.01); ***G06F 3/162*** (2013.01); ***G06F 3/165*** (2013.01); ***H04R 3/12*** (2013.01); *H04R 2201/025* (2013.01); *H04R 2201/405* (2013.01)

(57) **ABSTRACT**

A system and method is described for determining whether a loudspeaker device has relocated, tilted, rotated, or changed environment such that one or more parameters for driving the loudspeaker may be modified and/or a complete reconfiguration of the loudspeaker system may be performed. In one embodiment, the system may include a set of sensors. The sensors provide readings that are analyzed to determine 1) whether the loudspeaker has moved since a previous analysis and/or 2) a distance of movement and/or a degree change in orientation of the loudspeaker since the previous analysis. Upon determining the level of movement is below a threshold value, the system adjusts previous parameters used to drive one or more of the loudspeakers. By adjusting previous parameters instead of performing a complete recalibration, the system provides a more efficient technique for ensuring that the loudspeakers continue to produce accurate sound for the listener.